

CIRKEL- OCH SEKTORSPRIDARE PERROT P 1

UTFÖRANDE



DESCRIPTION

FEATURES
22° trajectory angle

MATERIAL
Pipe axle _____ stainless steel
Guide bush _____ stainless steel
Elbow _____ high quality plastic
Piston _____ brass & high quality plastic
Nozzle _____ aluminium/brass
Jet pipe _____ aluminium

AVAILABLE TYPES
P1 - full and part circle sprinkler
two-nozzles

CONNECTION
3" female thread

TECHN. DATA DETAIL

Spridardata gäller vid vindstilla förhållanden och lägsta rotationshastighet.

TECHNICAL DATA P1

diam nozzle	P (bar)	P (bar)	P (bar)	P (bar)	P (bar)
D1	3,0	4,0	5,0	6,0	7,0
mm	casting range mtr. *				
18 x 7	38,0	42,5	45,0	49,0	52,0
20 x 7	42,0	45,5	48,0	52,0	54,0
22 x 7	43,5	47,0	50,5	53,5	56,0
24 x 7	46,5	49,0	52,5	54,5	57,0
26 x 7	49,5	53,0	56,0	59,0	62,0
28 x 7	51,5	55,0	58,0	62,0	65,0
30 x 7	53,5	57,5	61,0	64,0	67,0
32 x 7	55,0	58,5	63,0	66,0	68,5
34 x 7	57,0	60,5	64,5	68,0	70,5
	water consumption Q _v (m ³ /h)				
18 x 7	22,98	26,54	29,67	32,50	35,11
20 x 7	27,67	31,95	35,72	39,13	42,26
22 x 7	32,84	37,92	42,40	46,45	50,17
24 x 7	38,51	44,47	49,72	54,46	58,83
26 x 7	44,67	51,58	57,67	63,18	68,24
28 x 7	51,33	59,27	66,26	72,59	78,41
30 x 7	58,48	67,52	75,49	82,70	89,32
32 x 7	66,12	76,35	85,36	93,50	101,00
34 x 7	74,25	85,74	95,86	105,01	113,42

* Casting range at lowest rotation time.